



SAFETY DATA SHEET

750ml SUPER PROFESSIONAL THICK BLEACH W2

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	750ml SUPER PROFESSIONAL THICK BLEACH W2
Product number	800-111-0013
Container size	1 litre
UFI	UFI: DMS7-PSQW-MH7Y-C3R4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Cleaning agent. Disinfectant.
Uses advised against	Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Supplier	Mirius™ A Coventry Group Company Woodhams Road Siskin Drive Coventry CV3 4FX Coventry Chemicals (Ireland) Limited 4th Floor 8-34 Percy Place Dublin 4 Ireland Tel: +44 (0) 02476 639 739 Fax: +44 (0) 02476 639 717 Email: sales@mirius.com
----------	--

Contact person	For content of safety data sheet: sds@mirius.com
----------------	--

1.4. Emergency telephone number

Emergency telephone	+44 (0) 1865407333 (Strictly for emergencies only: incidents involving damage to human health and/or the environment)
---------------------	---

National emergency telephone number

UK:
In case of a medical emergency following exposure to a chemical call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24
Ireland: For information or to report a poisoning incident contact The National Poisons Information Centre (01 8092166)


SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards	Met. Corr. 1 - H290
------------------	---------------------

750ml SUPER PROFESSIONAL THICK BLEACH W2

Health hazards	Skin Corr. 1C - H314 Eye Dam. 1 - H318
Environmental hazards	Aquatic Acute 1 - H400 Aquatic Chronic 2 - H411
2.2. Label elements	
Hazard pictograms	
	
Signal word	Danger
Hazard statements	<p>H290 May be corrosive to metals.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H400 Very toxic to aquatic life.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>
Precautionary statements	<p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 Immediately call a POISON CENTER/ doctor.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	EUH206 Warning! Do not use together with other products. May release dangerous gases (chlorine).
Contains	SODIUM HYPOCHLORITE, C12-14-ALKYL ETHER SULFATES
Biocide Labelling	This product contains substances with biocidal properties., Contains active substance: Sodium Hypochlorite, 4.37%, Read attached instructions before use.
Detergent labelling	< 5% anionic surfactants, < 5% chlorine-based bleaching agents, < 5% perfumes
Supplementary precautionary statements	<p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P102 Keep out of reach of children.</p> <p>P103 Read label before use.</p> <p>P234 Keep only in original packaging.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P363 Wash contaminated clothing before reuse.</p> <p>P390 Absorb spillage to prevent material damage.</p> <p>P391 Collect spillage.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

750ml SUPER PROFESSIONAL THICK BLEACH W2

SODIUM HYPOCHLORITE	4.4%
CAS number: 7681-52-9	EC number: 231-668-3
M factor (Acute) = 10	M factor (Chronic) = 1
Classification	
Ox. Liq. 2 - H272	
Met. Corr. 1 - H290	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	
C12-14 ALKYL ETHER SULFATES	1-5%
CAS number: 68891-38-3	EC number: 500-234-8
Classification	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Aquatic Chronic 3 - H412	
SODIUM HYDROXIDE	<1%
CAS number: 1310-73-2	EC number: 215-185-5
Classification	
Met. Corr. 1 - H290	
Skin Corr. 1A - H314	
Eye Dam. 1 - H318	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues. Rinse nose and mouth with water.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Skin contact	Remove contaminated clothing. Get medical attention if irritation persists after washing. Rinse immediately with plenty of water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel. Rinse immediately with plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	The product is not believed to present a hazard due to its physical nature. Prolonged or repeated exposure may cause the following adverse effects: Irritation.
Ingestion	This product is corrosive. May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

750ml SUPER PROFESSIONAL THICK BLEACH W2

Skin contact	Causes severe burns. Prolonged contact causes serious tissue damage.
Eye contact	This product is corrosive. May cause chemical eye burns. Corneal damage. Severe irritation, burning, tearing and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. Foam, carbon dioxide or dry powder.
-------------------------------------	---

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
---------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Contact with acids liberates toxic gas.
-------------------------	---

Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Chlorine. Hydrogen chloride (HCl). Oxides of carbon.
--------------------------------------	---

5.3. Advice for firefighters

Protective actions during firefighting	Control run-off water by containing and keeping it out of sewers and watercourses.
---	--

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes and clothing. For personal protection, see Section 8.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Collect and dispose of spillage as indicated in Section 13. Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Stop leak if safe to do so. Flush away spillage with plenty of water. Absorb spillage with non-combustible, absorbent material. Do not discharge into drains or watercourses or onto the ground. Absorb in vermiculite, dry sand or earth and place into containers. Do not use sawdust or other combustible material. Provide adequate ventilation. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.
--------------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see Section 13.
------------------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin and eyes. Avoid inhalation of vapours and spray/mists. Do not mix with acid.
--------------------------	--

750ml SUPER PROFESSIONAL THICK BLEACH W2

Advice on general occupational hygiene

Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using this product. Provide eyewash station. Wash promptly with soap and water if skin becomes contaminated. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of skin.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect from light. Store away from the following materials: Acids. Store at temperatures between 5°C and 25°C. Keep out of the reach of children.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

SODIUM HYPOCHLORITE

Short-term exposure limit (15-minute): WEL 0.5 ppm 1.5 mg/m³

SODIUM HYDROXIDE

Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit.

SODIUM HYPOCHLORITE (CAS: 7681-52-9)

DNEL

Industry - Inhalation; Long term local effects: 1.55 mg/m³
 Industry - Inhalation; Long term systemic effects: 1.55 mg/m³
 Industry - Inhalation; Short term local effects: 3.1 mg/m³
 Industry - Inhalation; Short term systemic effects: 3.1 mg/m³
 Consumer - Inhalation; Long term local effects: 1.55 mg/m³
 Consumer - Inhalation; Long term systemic effects: 1.55 mg/m³
 Consumer - Inhalation; Short term local effects: 3.1 mg/m³
 Consumer - Inhalation; Short term systemic effects: 3.1 mg/m³
 Consumer - Oral; Long term systemic effects: 0.26 mg/kg/day

PNEC

- Fresh water; 0.00021 mg/l
 - marine water; 0.000042 mg/l
 - Intermittent release; 0.00026 mg/l
 - STP; 4.69 mg/l
 - ;

C12-14 ALKYL ETHER SULFATES (CAS: 68891-38-3)

DNEL

Workers - Inhalation; Long term systemic effects: 175 mg/m³
 Workers - Dermal; Long term systemic effects: 2750 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 52 mg/m³
 Consumer - Dermal; Long term systemic effects: 1650 mg/kg/day
 Consumer - Oral; Long term systemic effects: 15 mg/kg/day

750ml SUPER PROFESSIONAL THICK BLEACH W2

PNEC	- Fresh water; 0.24 mg/l
	- marine water; 0.024 mg/l
	- Intermittent release; 0.071 mg/l
	- Sediment, Fresh water; 0.917 mg/kg
	- Sediment, marine water; 0.092 mg/kg
	- Soil; 7.5 mg/kg
	- STP; 10,000 mg/l

SODIUM HYDROXIDE (CAS: 1310-73-2)

DNEL	Industry - Inhalation; Long term local effects: 1.0 mg/m ³
	Consumer - Inhalation; Long term local effects: 1.0 mg/m ³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses. Personal protective equipment that provides appropriate eye and face protection should be worn.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Polyvinyl chloride (PVC). Rubber (natural, latex). To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. A break through time of >60 minutes is suggested. Gloves should be inspected regularly for damage.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact. Use appropriate skin cream to prevent drying of skin.

Hygiene measures

Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Use appropriate skin cream to prevent drying of skin.

Respiratory protection

Respiratory protection not required.

Environmental exposure controls

Avoid releasing into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Yellow. Clear.
Odour	Citrus. Chlorine.
Odour threshold	Not applicable.
pH	pH (concentrated solution): >11
Flash point	This product does not sustain combustion.

750ml SUPER PROFESSIONAL THICK BLEACH W2

Relative density	1.070 typically @ 20°C
Solubility(ies)	Soluble in water.
Viscosity	300-450 cP @ 20°C
Explosive properties	There are no chemical groups present in the product that are associated with explosive properties.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	There are no chemical groups present in the product that are associated with oxidising properties.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Other information	Not relevant.
--------------------------	---------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	The reactivity data for this product will be typical of those for the following class of materials: Acids. Alkalis. Oxidising materials.
-------------------	--

10.2. Chemical stability

Stability	Decomposes over time. Factors that increase the rate of decomposition: increase in temperature, certain metallic impurities, high initial concentration, fall in pH below 11 and exposure to light.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Generates toxic gas in contact with acid. Chlorine.
---	---

10.4. Conditions to avoid

Conditions to avoid	Avoid exposure to high temperatures or direct sunlight.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Acids. Ammonia. Organic compounds. Some metals. Nickel. Iron. Copper.
---------------------------	---

10.6. Hazardous decomposition products

Hazardous decomposition products	Chlorine. Hydrogen chloride (HCl). Oxides of the following substances: Chlorine. Hypochlorous acid. Sodium chlorate
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	Information given is based on data of the components and of similar products.
------------------------------	---

Other health effects	Does not contain any substances known to be carcinogenic.
-----------------------------	---

Acute toxicity - oral

Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
-------------------------------------	--

Acute toxicity - dermal

Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
---------------------------------------	--

Acute toxicity - inhalation

750ml SUPER PROFESSIONAL THICK BLEACH W2

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Corrosive to skin.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Corrosivity to eyes is assumed.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Not sensitising. Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	Not classified. Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Does not contain any substances known to be mutagenic.
<u>Carcinogenicity</u>	
Carcinogenicity	Does not contain any substances known to be carcinogenic.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Does not contain any substances known to be toxic to reproduction.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Inhalation	The product is considered to be a low hazard under normal conditions of use. Prolonged or repeated exposure may cause the following adverse effects: Irritation.
Ingestion	Small amounts may cause serious damage. May cause chemical burns in mouth, oesophagus and stomach. Stomach pain. Nausea, vomiting. Diarrhoea.
Skin contact	Causes severe skin burns and eye damage. Prolonged or repeated exposure may cause the following adverse effects: Dryness and/or cracking. Redness. Irritation. Chemical burns.
Eye contact	Causes severe skin burns and eye damage. May cause temporary eye irritation. May cause chemical eye burns.
11.2 Information on other hazards	
11.2.1. Endocrine disrupting properties	This product is not classified as, nor contains substances classed as having endocrine disrupting characteristics at levels >0.1% by weight (according to Regulation (EU) 2018/605).
11.2.2 Other information	None known

Toxicological information on ingredients.

SODIUM HYPOCHLORITE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 8,910.0

Species Rat

Notes (oral LD₅₀) REACH dossier information.

750ml SUPER PROFESSIONAL THICK BLEACH W2

ATE oral (mg/kg) 8,910.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,001.0

Species Rabbit

ATE dermal (mg/kg) 2,001.0

Skin corrosion/irritation

Animal data Corrosive to skin. REACH dossier information. Dose: LD50 = 20g/kg bw, 2 days, Rabbit

Serious eye damage/irritation

Serious eye damage/irritation Corrosivity to eyes is assumed.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vivo REACH dossier information. Negative.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility REACH dossier information. No evidence of reproductive toxicity in animal studies.

SECTION 12: Ecological information

Ecotoxicity The product contains a substance which is very toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity The product contains a substance which is harmful to aquatic organisms.

Ecological information on ingredients.

SODIUM HYPOCHLORITE

Acute aquatic toxicity

LE(C)₅₀ 0.01 < L(E)C50 ≤ 0.1

M factor (Acute) 10

Acute toxicity - fish EC₅₀, 96 hours: 0.01-0.1 mg/l,

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 0.01-0.1 mg/l, Daphnia magna

Acute toxicity - microorganisms LOEC, : 0.375 mg/l, Activated sludge

750ml SUPER PROFESSIONAL THICK BLEACH W2

Chronic aquatic toxicity

NOEC	0.001 < NOEC ≤ 0.01
Degradability	Rapidly degradable
M factor (Chronic)	1

12.2. Persistence and degradability

Persistence and degradability The product contains inorganic substances which are not biodegradable. May accumulate in soil and sediment. Substantially removed in biological treatment processes. The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in The Detergents Regulations (as amended).

Ecological information on ingredients.

SODIUM HYPOCHLORITE

Stability (hydrolysis)	Water - Half-life 10% NaOCl: 220 days @ 25°C - Half-life 5% NaOCl: 790 days @ 25°C REACH dossier information.
Biodegradation	The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients.

SODIUM HYPOCHLORITE

Bioaccumulative potential	Low potential for bioaccumulation.
Partition coefficient	log Kow: -3.4174 REACH dossier information.

12.4. Mobility in soil

Mobility The product is water-soluble and may spread in water systems.

Ecological information on ingredients.

SODIUM HYPOCHLORITE

Henry's law constant	0.076 @ 20°C
-----------------------------	--------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Endocrine disrupting properties

Endocrine disrupting properties This product is not classified as, nor contains substances classed as having endocrine disrupting characteristics at levels >0.1% by weight (according to Regulation (EU) 2018/605).

Ecological information on ingredients.

SODIUM HYPOCHLORITE

750ml SUPER PROFESSIONAL THICK BLEACH W2

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current UK criteria.

12.6. Other adverse effects

Other adverse effects There is evidence that sodium hypochlorite inhibits the aerobic treatment process at a concentration of 0.05 mg/l.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Dispose of waste product or used containers in accordance with local regulations

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1760
UN No. (IMDG)	1760
UN No. (ICAO)	1760
UN No. (ADN)	1760

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYPOCHLORITE, C12-14-ALKYL ETHER SULFATES)
Proper shipping name (IMDG)	CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYPOCHLORITE, C12-14-ALKYL ETHER SULFATES)
Proper shipping name (ICAO)	CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYPOCHLORITE, C12-14-ALKYL ETHER SULFATES)
Proper shipping name (ADN)	CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYPOCHLORITE, C12-14-ALKYL ETHER SULFATES)

14.3. Transport hazard class(es)

ADR/RID class	8
ADR/RID classification code	C9
ADR/RID label	8
IMDG class	8
ICAO class/division	8
ADN class	8

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III

750ml SUPER PROFESSIONAL THICK BLEACH W2

ICAO packing group III

ADN packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-B

ADR transport category 3

Emergency Action Code 2X

Hazard Identification Number (ADR/RID) 80

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	<p>The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).</p> <p>The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).</p> <p>EH40/2005 Workplace exposure limits.</p> <p>Health and Safety at Work etc. Act 1974 (as amended).</p> <p>The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].</p> <p>The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019 (as amended).</p> <p>The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).</p> <p>The Detergents Regulations 2010 (SI 2010 No. 740) (as amended). The Detergents (Amendment) (EU Exit) Regulations 2019 (SI 2019 No. 612) (as amended). The Detergents (Safeguarding) (Amendment) (EU Exit) Regulations 2019 (SI 2019 No. 671) (as amended).</p> <p>The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 (SI 2020 No. 1577) (as amended).</p>
-----------------------------	--

750ml SUPER PROFESSIONAL THICK BLEACH W2

EU legislation

European Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (as amended)
 European Regulation (EC) No 1907/2006 - Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended)
 European Regulation (EC) No 648/2004 on detergents (as amended)
 European Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products (BPR) as amended
 Regulation (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) 1907/2006.

Guidance

COSHH Essentials.
 ECHA Guidance on the Application of the CLP Criteria.
 ECHA Guidance on the compilation of safety data sheets.
 Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

A chemical safety assessment has been carried out. Sodium hypochlorite. and Sodium hydroxide.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

PBT: Persistent, Bioaccumulative and Toxic substance.
 vPvB: Very Persistent and Very Bioaccumulative.
 MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.
 PNEC: Predicted No Effect Concentration.
 DNEL: Derived No Effect Level.

Revision comments

NOTE: Lines within the margin indicate significant changes from the previous revision. Review of SDS with no change of classification. Note: Finished product SDS take their revision history from the parent bulk liquid SDS. The revision data will show that of the parent liquid.

Revision date 21/03/2024

Revision 2

Supersedes date 20/02/2019

SDS number 22054

Hazard statements in full

H272 May intensify fire; oxidiser.
 H290 May be corrosive to metals.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.